



JL&L TREND TOOLS WHOLESALING



## TEKTrend-AZ8922 Sound Level Meter



- Meets IEC60651, type 2 class standard
- Deluxe super large LCD display with affordable price
- Unique background noise absorber
- Features with digital display and analog bar graph
- Auto/manual range, 6 measurement range in 10 steps
- Max Hold and Fast/Slow response mode
- A/C weighting is switchable
- Easy to calibrate by standard calibrator
- AC/DC analog output

Measure Range	A weight: 30~130 dB
C weight: 35~130 dB	
Digital Display (6 ranges)	30~80, 40~90, 50~100, 60~110, 70~120, 80~130 dB
Digital Display Resolution	0.1 dB
Digital Updating Time	160 ms
Quasi-analog Bar (6 ranges)	30~80, 40~90, 50~100, 60~110, 70~120, 80~130 dB
Quasi-analog Resolution	1 dB
Bar Updating Time	40 ms
Accuracy at 94 dB, 1KHz	±1.5 dB
Analog Output	AC 0.707 Vrms (at full scale): DC 10 mV/dB
Microphone	Dia 6mm electric condenser microphone
Frequency Range	31.5 Hz~8 KHz
Battery Life Time	30 hours typical
Windscreen	YES
LCD Size	62(L) * 42(W) mm
LCD Backlight	YES
Operating Temperature	0~50°C
Operating RH%	Humidity < 80%
Storage Temperature	-20~50°C
Storage RH%	Humidity < 90%
Meter Size	254(L) * 77(W) * 37(H) mm
Weight	~200g
Battery	9V Battery * 1 PC or 9V DC adaptor
Standard Package	Meter, Battery, Manual, Carry Case

JL&L Trend Tools Wholesaling

8637-9119, 8542-9406 [jlbl@jblsource.com](mailto:jlbl@jblsource.com) [www.jblsource.com](http://www.jblsource.com)